

# Instructions for wiring FK Passat Angel Eye Headlights

\*U.S. Spec cars do not require the use of any additional wiring or parts not already found on your car\*

-Step 1

Locate the electrical plug on the back of your headlight. - Disconnect it from the headlight.



-Step 2

Roll back the rubber boot and slide it back a few inches, out of the way.



-Step 3

Locate the small white wire with the green stripe (this is what will power the angel eyes)



-Step 4

Using a small screwdriver or hook tool, push in the two clips on each side of the purple section on the back of the plug, and gently slide the purple section to the side very slightly. This will release the pins on the end of your headlight wires from the connector. **IMPORTANT:** Note current locations of wires before removing anything, in case a wire which should not come out, is accidentally removed.



-Step 5

This is how it will look once the purple "locking" section is free.



-Step 6

You will be moving the white/green wire from the pin location it is currently in, to the location shown here. (currently empty)



-Step 7

Gently remove the small white/green wire from it's current location, and move it to the empty location on the other side of the brown (ground) wire.



-Step 8

Gently push the white/green wire and pin down into the hole until it "clicks" into place.



- Step 9

Push the purple section back in until it "snaps" back into place. Move the rubber boot back into place.



-Step 10

Install the plug onto the back of your new FK Headlight.



Since the E-Code angel eye headlight no longer has a driving light , your driving light function (headlights on and one click out on the switch) will engage the angel eye function.

